

## SELECTION CHARTS

### DIRECTIONAL ARROWS

FEATURE	24 X 48	30 X 60	36 X 72	48 X 96	MINI ARROW	MAXI ARROW
10 LAMP					•	
13 LAMP	•	•				
14 LAMP						•
15 LAMP		•	•	•		
25 LAMP		•	•	•		
LOW PROFILE	•	•	•			
180°		•	•			
MANUAL LIFT	•	•	•			
POWER LIFT	•	•	•			
HALOGEN	•	•	•	•	•	•
LED	•	•	•	•	•	•
M100 CONTROL	•	•	•	•		



### MESSAGE SIGNS

FEATURE	# OF LINES	CHARACTERS PER LINE	GRAPHICS	DISPLAY SIZE	CHARACTER SIZE-MAX	CHARACTER SIZE - MIN	LIFT MECHANISM	# OF MESSAGES - USER	CELLULAR READY	RADAR READY
<b>SR 190</b>	4 <sup>2</sup>	13 <sup>2</sup>	•	48"H 94"W	40 <sup>2</sup>	9	WNCH	50 <sup>3</sup>	•	•
<b>SR 290</b>	4 <sup>2</sup>	13 <sup>2</sup>	•	48"H 96"W	40 <sup>2</sup>	9	HYD	50 <sup>3</sup>	•	•
<b>SR 380</b>	3	8	N/A	78"H 128"W	18	18	HYD	50 <sup>3</sup>	•	•
<b>SR 345</b>	3	11	• <sup>1</sup>	78"H 128"W	18	18	HYD	50 <sup>3</sup>	•	•
<b>SR 390</b>	4 <sup>2</sup>	13 <sup>2</sup>	•	78"H 128"W	68 <sup>2</sup>	11	HYD	50 <sup>3</sup>	•	•

<sup>1</sup> Limited graphics per line

<sup>2</sup> In graphics mode depending on font used.

<sup>3</sup> (4) pages in each message. Up to (10) using VMS Central.

<sup>4</sup> (2) messages of (4) pages each form one sequence. Up to (8) sequences of (10) pages using VMS Central.